

The Mfg. of Advanced Textiles & Technical Textiles

SHREE TECHNO AND COMPOSITE LLP

SHREE TECHNO AND COMPOSITE LLP DATA SHEET		
GSM	370	+/- 5 %
WIDTH	1000 mm	+/- 5 MM
WEFT	Glass Fiber	300 TEX
WARP	Kevlar fiber	167 TEX
THICKNESS	0.4	0.1MM
WEAVE	PLAIN /TWILL / SATIN	
NOTE :- ABOVE TDS IS STANDARD, WE CAN	ALSO MANUFACTURING CUSTOMIZED PRODUCT AS PER APPLICA	ATION AND CUSTOMERS REQUIREMENT.
GLASS FIBER		
LINEAR DENSITY	276 - 324	TEX
ELONGATION AT BREAK	0.45 - 0.85	%
NOTE :- ABOVE CARBON FIBER TDS IS AS PER CARBON FIBER SUPPLIER GIVEN C. FIBER TDS.		
KEVLAR FIBER 1000 AF		
YARN TYPE	167	TEX
MODULUS	70 +/- 7	GPa
ELONGATION AT BREAK	3.7 +/- 0.5	%
NOTE :- ABOVE CARBON FIBER TDS IS AS PER CARBON FIBER SUPPLIER GIVEN C. FIBER TDS.		

Address: 10/330, Sarvoday Nagar, Ichalkaranji - 416115

Dist. Kolhapur (Maharashtra), India

Email: info@shreebumbgroup.com

Mobile: (+91) 9371100920

Landline: (+91) 230 2438183

Website: www.shreebumbgroup.com