

The Mfg. of Advanced Textiles & Technical Textiles

## SHREE TECHNO AND COMPOSITE LLP

SHREE TECHNO AND COMPOSITE LLP  DATA SHEET		
GSM	370	+/- 5 %
WIDTH	1000 mm	+/- 5 MM
WEFT	Carbon fiber	12K
WARP	Kevlar fiber	330 TEX
THICKNESS	0.4	0.1 MM
WEAVE	PLAIN /TWILL / SATIN	
NOTE :- ABOVE TDS IS STANDARD, WE CAN	ALSO MANUFACTURING CUSTOMIZED PRODUCT AS PER APPLICA	ATION AND CUSTOMERS REQUIREMENT.
	CARBON FIBER 12K	
TENSILE STRENGTH	4400 -4900 - 5500	MPA
LINEAR DENSITY	760 - 800	TEX
DENSITY	1.75 - 1.81	G/CM <sup>3</sup>
TENSILE MODULUS	230 - 250	Gpa
ELONGATION AT BREAK	1.8 – 2.2	%
NOTE :- ABOVE	I CARBON FIBER TDS IS AS PER CARBON FIBER SUPPLIER GIVEN C	. FIBER TDS.
В	KEVLAR FIBER 1000 AF	P
YARN TYPE	330	TEX
MODULUS	74 +/- 11	GPa
ELONGATION AT BREAK	3.9 +/- 0.5	0/0
NOTE :- ABOVE	I CARBON FIBER TDS IS AS PER CARBON FIBER SUPPLIER GIVEN C	. FIBER TDS.

Address: 10/330, Sarvoday Nagar, Ichalkaranji - 416115

Dist. Kolhapur (Maharashtra), India

Email: info@shreebumbgroup.com

Mobile: (+91) 9371100920

Landline: (+91) 230 2438183

Website: www.shreebumbgroup.com